

Hitouch 6

HN21-60HT

590-610W

BIFACIAL

Bifacial Module

21.55%

Maximum Efficiency

15 YEARS

Product Warranty



Higher Power Output

Higher module conversion efficiency benefit from bigger wafer and half-cell structure.

MBB technology enhances current collection with lower series resistance.



Excellent Temperature Coefficient

Lower operating temperature and temperature coefficient increases the power output



Long-Term Reliability

Module certified to withstand extreme wind (2400 Pascal) and snow loads (5400 Pascal).

Excellent anti-PID performance to guarantee a better sustainability in harsh environment.




Lower Hot Spot and Crack Risk

Reduce hot-spot risk with optimized electrical design and lower operating current.

Reduce crack risk by MBB solar cell design.

Power Warranty



15-year product warranty



30-year linear power output warranty

Insurance



Munich RE



太平洋保险 CPIC

Certificates



About Hanersun

Hanersun is a world leading solar module manufacturer and comprehensive energy solution provider. We provide customers with cutting edge solar modules, and services for the entire project life cycle.

Electrical Characteristics

Module Type	HN21-60HT590W		HN21-60HT595W		HN21-60HT600W		HN21-60HT605W		HN21-60HT610W	
	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
Maximum Power (Pmax)	590	442	595	446	600	450	605	456	610	460
Maximum Power Voltage (Vmp)	34.50	32.30	34.70	32.50	34.90	32.70	35.10	32.90	35.30	33.20
Maximum Power Current (Imp)	17.11	13.70	17.15	13.73	17.20	13.77	17.25	13.82	17.29	13.86
Open-circuit Voltage (Voc)	40.90	38.70	41.10	38.80	41.30	39.00	41.50	39.20	41.70	39.60
Short-circuit Current (Isc)	18.37	14.80	18.42	14.85	18.47	14.89	18.52	14.94	18.56	15.02
Module Efficiency(%)	20.80%		21.00%		21.20%		21.40%		21.55%	

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5.
*Measuring tolerance: 0 ~ +5W

NMOT: Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s.

Electrical Characteristics with 10% Solar Irradiation Ratio

Module Type	HN21-60HT590W	HN21-60HT595W	HN21-60HT600W	HN21-60HT605W	HN21-60HT610W
Maximum Power (Pmax)	649	655	660	665	670
Maximum Power Voltage (Vmp)	34.50	34.70	34.90	35.10	35.30
Maximum Power Current (Imp)	18.82	18.88	18.92	18.97	18.98
Open-circuit Voltage (Voc)	40.90	41.10	41.30	41.50	41.70
Short-circuit Current (Isc)	20.21	20.26	20.32	20.37	20.42

Mechanical Parameters

Solar Cells	Monocrystalline (210mm)
Module Dimensions	2172*1303*30mm
Glass	2mm-2mm
Frame	Anodized Aluminium Alloy
Output Cable	4.0mm ² , 300/300mm

No. of Cells	120 [2 x (10 x 6)]
Weight	34.4kg
Encapsulant Material	EVA/POE
J-Box	IP68
Connector	MC4 Compatible

Temperature Ratings

NMOT (Nominal operating cell temperature)	45°C(±2°C)
Temperature Coefficient of Pmax	-0.349%/°C
Temperature Coefficient of Voc	-0.274%/°C
Temperature Coefficient of Isc	+0.050%/°C

(Do not connect Fuse in Combiner Box with two or more strings in parallel connection)

Operating Parameters


Operational Temperature	-40°C~+85°C
Maximum System Voltage	1500V DC (IEC)
Maximum Series Fuse Rating	35A
Bifacility	75%-80%

Packaging


Pcs per Pallet: 36

Pcs per 40' HC: 648


I-V Curves of PV Module (600W)




P-V Curves of PV Module (600W)



Dimensions (Unit: mm)



Front View



Back View